

## **Giant Contact S/Contact Switch Dropper Post Fit Guide**

## Find the Giant dropper seatpost length that best fits your bicycle frame

## **Frame & Seatpost Measurements**

Measure Rider Seat Height (A)

Install any seatpost into your frame and set it to your desired standard riding height.

Measure the distance from the top of the seat tube to the bottom of the saddle rails at the clamp. Record this measurement (A) in the circle to the right.









Install any seatpost into your frame and set it to its maximum insertion.

Mark the seatpost where it enters at the top of the


Remove the seatpost and measure from this mark to the base of the seatpost.

Record this measurement (B) in the circle to the right.









## **Measurement Calculation**

Use your measurements (A) and (B) along with the Contact S/ Switch measurements in the chart below to determine the optimal seatpost length and travel for your riding needs and frame size. For your safety, it is essential that your frame meets the minimum seatpost insertion.

Confirm that your frame meets the minimum seatpost insertion:













Confirm that exposed seatpost length does not exceed rider seat height:







Determine the shortest length seatpost you can use:











Determine the longest length seatpost you can use:















Travel	DSP (mm)	C Total Post Length	D Minimum Exposed Length	
75	196.6	295	127.4	
100	219.6	345	154.4	
125	244.6	395	179.4	
150	265.6	440	203.4	
170	266.1	455	217.9	

DSP 80



A 455mm length post C DOES NOT WORK if A + B > 484mm.





